

TB-STD 1300 & 2300

TB-STD is an air-driven, manually operated production test bench with water as the test medium. TB-STD brings world class safety to workshop test bench category with stainless steel testroom, double walls, 12 mm safety glass and Quick stop.

TB-STD offers a large test room with an adjustable turntable return test connection.

EasyLogging creates instant test certificate after each test.

TECHNICAL DATA		
Test connection		1 1/8-12-UNF-HP (F)
Testroom		Stainless steel
Pressure range (bar/psi)	TB-STD 1300	135 – 1 300 / 1959 – 18854
Pressure range (bar/psi)	TB-STD 2300	180 – 2260 / 2611 – 32 778
Flow (lpm/cuim @ 0 bar)	TB-STD 1300	1.4 / 85.0
Flow (lpm/cuim @ 0 bar)	TB-STD 2300	1.0 / 61.0
Test pressure gauge (bar/psi)	TB-STD 1300	0 - 1 600 / 0 - 25 000
Test pressure gauge (bar/psi)	TB-STD 2300	0 - 2 500 / 0 - 36 250
Test medium		Water from tap
Max hose length		Depends on bend radius
Door operation		Manual with gas springs
Door locking		Air driven
Incoming air pressure min.		7 bar to reach max test pressure
DIMENSIONS (LxWxH)		
Test Area (mm)	2500x890x270 (front) 510 (back)	
Test Area (inches)	98.4x35.0x10.6 (front) 20.1 (back)	
External (mm)	3280x1000x1330	
External (inches)	129.1x39.4x52.4	
WEIGHT (KG/LBS)		
Approximately 870 / 1918		

ORMANLAR High Tech Hose Solutions

Hose Fittings Assembly

CONTROL

Manual Air-driven

STANDARD FEATURES

Air-driven pump with start/stop Test fluid inlet valve and inlet filter

Quick stop (opens bleed valve and stops the pump) Pressure regulator

Air and high pressure gauge

Bleed valve

Isolate valve

SoftBleed (de-energizer)

Adjustable turntable return test connection

EasyLogging Instant Reporting*

Laptop holder

Test adaptor: 2 pcs. 1 1/8"-12UNF-HP (M) to 1/2" BSP (F)

 * Including pressure sensor 0 – 1 500 bar with accuracy of +/- 0,25% (+/- 3,75 bar) for full scale with calibration certificate

OPTIONS


Extra gauge 0 - 250 bar (TB033.009) QuickConnect 'Exchange' QCE 1000 (TB122.001) QuickConnect 'Exchange' QCE 2000 (TB123.001) Manifold set for 4 hoses, QCM 4x½" BSP (F) (TB148.001)

Fast filling (TB141.002)

Other language than standard (TB104.002)









83