CONTROL

SCC (5" touchscreen)

OPTIONS

Foot pedal

Mechanical back stop device

Electrical back stop device

Tool base (20 slots) with QuickChange-tool Tool rack (12 slots) with QuickChange-tool








Tool base and Tool rack with QuickChange-tool as an option.

DieSetNo	D (mm)	L (mm)	Crimp. range (mm
18013/10	10	55	10.0-12.0
18013/12	12	55	12.0-14.0
18013/14	14	55	14.0-16.0
18013/16	16	55	16.0-19.0
18013/19	19	55	19.0-23.0
18013/23	23	55	23.0-27.0
18013/27	27	70	27.0-31.0
18013/31	31	70	31.0-36.0
18013/36	36	75	36.0-41.0
18013/41	41	75	41.0-47.0
18013/47	47	85	47.0-54.0
18013/54	54	85	54.0-61.0





P₂OSCC


Finn-Power P2OSCC is strong, fast and reliable crimping machine for any service crimping need.

This model turns hydraulics off to conserve energy, and to reduce workplace noise levels whenever the machine is idle.

SCC control brings smartness to workshop crimpers via connectivity and visual user interface, including step crimping as a standard feature. Optional single foot pedal can be connected to workshop SCC models.

TECHNICAL DATA	
Max crimping dia (mm) 1)	61
Max crimping dia (inch) 1)	2.40
Max crimping force (kN)	1370
Max crimping force (tonnage)	137
Cycle time 10 mm (s) 2) 3)	3.6/10.3
Hose size ID (inch)	1 ½ *
Die set series	20
Max opening (mm) 4)	+25
Max opening without dies (mm)	109
Master die D/L (mm)	84/80
Master die D/L (inch)	3.31/3.15
Motor Power (kW/HP) 3)	3.0/4.0 1.5/2.0
Oil tank volume	27 I
DIMENSIONS (LxWxH)	
(mm)	650x510x757
(inch)	25.6x20.1x29.8
WEIGHT (KG/LBS)	
137/309	





With standard dies. Crimping range can be increased with special dies. Theoretical with 10 mm cycle.

3-phase/1-phase
Maximum opening is the total die travel. Add
this value to the minimum crimping diameter
of the die set used. The result is the maximum
opening of the machine with die set in place.

