

P32SCC

Finn-Power P32SCC is strong, fast and reliable crimping machine for any service crimping need.


This model turns hydraulics off to conserve energy, and to reduce workplace noise levels whenever the machine is idle.

SCC control brings smartness to workshop crimpers via connectivity and visual user interface, including step crimping as a standard feature. Optional single foot pedal can be connected to workshop SCC models.

<u>'</u>	<u>'</u>	
TECHNICAL DATA		
Max crimping dia (mm) 1)	87	
Max crimping dia (inch) 1)	3.42	
Max crimping force (kN)	2000	
Max crimping force (tonnage)	200	
Cycle time 10 mm (s) 2) 3)	4.0/16.1	
Hose size ID (inch)	2 *	
Die set series	32	
Max opening (mm) 4)	+33	
Max opening without dies (mm)	132	
Master die D/L (mm)	99/80	
Master die D/L (inch)	3.90/3.15	
Motor Power (kW/HP) 3)	4.0/1.5 5.5/2.0	
Oil tank volume	27 I	
DIMENSIONS (LxWxH)		
(mm)	675x520x757	
(inch)	26.6x20.4x29.8	
WEIGHT (KG/LBS)		
194/427		

* ACCORDING TO THE FITTING.





With standard dies. Crimping range can be increased with special dies. Theoretical with 10 mm cycle.

3-phase/1-phase
Maximum opening is the total die travel. Add
this value to the minimum crimping diameter
of the die set used. The result is the maximum opening of the machine with die set in place.

Hose Fittings Assembly

CONTROL SCC (5" touchscreen) **OPTIONS** Foot pedal Mechanical back stop device Electrical back stop device Tool base (20 slots) with QuickChange-tool Tool rack (16 slots) with QuickChange-tool



DIE SET 32-SERIES			
DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
18506/10	10	55	10.0-12.0
18506/12	12	55	12.0-14.0
18506/14	14	55	14.0-16.0
18506/16	16	55	16.0-19.0
18506/19	19	55	19.0-22.0
18506/22	22	70	22.0-26.0
18506/26	26	70	26.0-30.0
18506/30	30	70	30.0-34.0
18506/34	34	75	34.0-39.0
18506/39	39	75	39.0-45.0
18506/45	45	90	45.0-51.0
18506/51	51	90	51.0-57.0
18506/57	57	100	57.0-63.0
18506/63	63	110	63.0-69.0
18506/69	69	110	69.0-75.0
18506/74	74	110	74.0-80.0
18506/78	78	110	78.0-87.0
In addition to of special d			sets, a wide range on request.









www.ormanlar.com.tr