

### PH 280 - WATER BLAST 30

Applicable Standard : Polyhose proprietary product / EN 1829 -2

#### Construction

**Core** Black colour, Synthetic rubber resistant to oil and water

**Reinforcement** Four high tensile steel wire spirals

**Cover** Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone

**Application** Water blasting, Water jetting, cleaning equipment. Delivery of water and water emulsions



Item Code	Dash Size	DN	ID		RI OD		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	kg/m
PH280-04	-04	06	1/4	6.4	0.58	14.7	0.70	17.9	12325	850	30815	2125	5.12	130	0.627
PH280-06	-06	10	3/8	9.5	0.69	17.5	0.83	21.1	12325	850	30815	2125	6.10	155	0.838
PH280-08	-08	12	1/2	12.7	0.84	21.3	0.97	24.6	12325	850	30815	2125	7.87	200	1.184
PH280-12	-12	19	3/4	19.0	1.17	29.8	1.29	32.8	12325	850	30815	2125	9.84	250	2.024
PH280-16	-16	25	1	25.4	1.38	35.1	1.51	38.3	12325	850	30815	2125	11.81	300	2.447



**Temperature Range:** Continuous: -40°C to +90°C

+90 216 5278751

+90 532 1606148

www.ormanlar.com.tr



MERKEZ

Istanbul Anadolu Yakası İMES Sanayi Sitesi A Blok 103 Sk.  
No:4 34775 Y.Dudullu - Ümraniye / Istanbul , TÜRKİYE